StarTech.com Cavo di Ricarica USB-A a USB-C da 3m, 15W (3A), Guaina con Doppio Strato Intrecciato in Nylon/TPE, Robusto Cavetto da USB-A 2.0 a USB Type-C



Marchio : StarTech.com

Codice prodotto: USB2AC3MBR

Nome del prodotto : Cavo di Ricarica USB-A a USB-C da 3m, 15W (3A), Guaina con Doppio Strato Intrecciato in Nylon/TPE, Robusto Cavetto da USB-A 2.0 a USB Type-C

StarTech Cavo di Ricarica USB-A a USB-C da 3m, 15W (3A), Guaina con Doppio Strato Intrecciato in Nylon/TPE, Robusto Cavetto da USB-A 2.0 a USB Type-C
StarTech.com Cavo di Ricarica USB-A a USB-C da 3m, 15W (3A), Guaina con Doppio Strato Intrecciato in Nylon/TPE, Robusto Cavetto da USB-A 2.0 a USB Type-C. Lunghezza cavo: 3 m. Connettore 1: USB A, Connettore 2: USB C, Versione USB: USB 2.0, Massima velocità di trasferimento: 0,48 Gbit/s, Placcatura contatti: Nichel, Colore del prodotto: Nero



Caratteristiche	
Versione USB *	USB 2.0
Connettore 1 *	USB A
Connettore 2 *	USB C
Genere del connettore 1 *	Maschio
Genere del connettore 2 *	Maschio
Fattore di forma del connettore 1	Dritto
Fattore di forma del connettore 2	Dritto
Dimensione del cavo AWG	28/21
Placcatura contatti	Nichel
Materiale del rivestimento del cavo	Elastomero Termoplastico (TPE), Nylon
Tipo di rivestimento del cavo	Intrecciato
Massima velocità di trasferimento	0,48 Gbit/s
Tipo di cavo	Cavo tondo
Plug & Play	✔
Alimentazione USB	✔
Fornitura di alimentazione USB fino a	15 W
Colore del prodotto *	Nero

Gestione energetica	
Corrente di ingresso (max)	3 A
Dimensioni e peso	
Lunghezza cavo *	3 m
Diametro del cavo	4,5 mm
Peso	93 g
Dati su imballaggio	
Larghezza imballo	140 mm
Profondità imballo	130 mm
Altezza imballo	25 mm
Peso dell'imballo	118 g
Contenuto dell'imballo	
Quantità per pacco *	1 pz
Condizioni ambientali	
Intervallo temperatura di funzionamento	-20 - 40 °C
Intervallo di temperatura	-20 - 70 °C
Certificati di sicurezza	
Certificati di conformità	CE
Dati logistici	
Quantità per cartone principale	80 pz
Larghezza scatola principale	540 mm
Lunghezza del cartone principale	320 mm
Altezza scatola principale	300 mm

0065030927741

065030927741

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 23-SEP-2026. Prints or copies of Information are only valid on the printed Publication date