



Dahua Technology VTO4202F-P-S2 Video-Zugangssystem 2 MP Silber

Marke : Dahua Technology

Artikel-Code: DHI-VTO4202F-P-S2

Produktname : VTO4202F-P-S2

Dahua Technology VTO4202F-P-S2. Unterstützte Videoformate: H.265. Megapixel (ca.): 2 MP, Unterstützte Video-Modi: 720p, 1080p, Sensor-Typ: CMOS. LED Typ: IR. Sprachcodec: G.711a, G.711u, PCM. Produktfarbe: Silber, Internationale Schutzart (IP-Code): IP65, IK-Kodex: IK07



Technische Details		Design	
Übertragungstechnik *	Kabelgebunden	Gehäusematerial	Aluminium
Farbe *	✗	Steuerung	Tasten
Freisprecheinrichtung *	✓	Unterstützte Positionierung	Senkrecht
Maximum Anzahl der unterstützten kameras *	1	Vorgesehene Verwendung	Draußen
Türstationsteuerung	✓	Netzwerk	
VoIP Protokolle	SIP, P2P, IPv4, FTP, UPnP, DNS, DDNS, RTSP, RTP, TCP, UDP	Ethernet Schnittstellen Typ	Schnelles Ethernet
Wandmontage	✓	Ethernet LAN Datentransferraten	10,100 Mbit/s
Eingebautes Mikrofon	✓	Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1
Automatische Gewinnkontrolle	✓	Verkabelungstechnologie	10/100Base-T(X)
Bewegungserfassungsfunktion	✓	Power over Ethernet (PoE)	✓
RFID-Lesegerät	✓	Unterstützte Netzwerkprotokolle	SIP, P2P, IPv4, FTP, UPnP, DNS, DDNS, RTSP, RTP, TCP, UDP
Nachhaltigkeitskonformität	✓	Software	
Nachhaltigkeitszertifikate	CE, Eidgenössische Kommunikationskommission (FCC)	Installiertes Betriebssystem	Linux
Bildschirm		Energie	
Unterstützte Videoformate	H.265	Außengerät Stromversorgung	Gleichstrom
Kamera		Netzteil Ausgangsspannung	48 V
Megapixel (ca.)	2 MP	AC-Adapter Ausgangsstrom	1 A
Unterstützte Video-Modi	720p, 1080p	Stromverbrauch (Standardbetrieb)	12 W
Sensor-Typ	CMOS	Betriebsbedingungen	
Größe des Bildsensors	25,4 / 2,5 mm (1 / 2.5")	Betriebstemperatur	-30 - 60 °C
Maximale Framerate	30 fps	Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Bildwinkel, horizontal	168,6°	Gewicht und Abmessungen	
Bildwinkel, vertikal	87,1°	Breite	100 mm
Nachtsicht		Tiefe	36 mm
Nachtsicht	✓	Höhe	100 mm
LED Typ	IR	Gewicht	350 g
Audio		Verpackungsdaten	
Eingebaute Lautsprecher	✓	Inklusive Außengerät *	✓
Aktive Geräuschunterdrückung	✓		

Audio		Verpackungsdaten	
Sprachcodec	G.711a, G.711u, PCM	Paketgewicht	400 g
Design		Logistikdaten	
Produktfarbe *	Silber	Menge pro Packung	1 Stück(e)
Internationale Schutzart (IP-Code)	IP65	Mindestbestellmenge	1 Stück(e)
IK-Kodex	IK07		



6939554951251

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-JUL-2024. Prints or copies of Information are only valid on the printed Publication date