StarTech.com Cavo Ethernet Cat6A Ultra Slim da 1 m Nero, UTP, Rame Puro 34AWG, Cavo di Rete Patch RJ45 Ultra Sottile, Testato Singolarmente




Marchio : StarTech.com

Codice prodotto:
N6APATUTP34BKS1M

Nome del prodotto : Cavo Ethernet Cat6A Ultra Slim da 1 m Nero, UTP, Rame Puro 34AWG, Cavo di Rete Patch RJ45 Ultra Sottile, Testato Singolarmente

StarTech Cavo Ethernet Cat6A Ultra Slim da 1 m Nero, UTP, Rame Puro 34AWG, Cavo di Rete Patch RJ45 Ultra Sottile
StarTech.com Cavo Ethernet Cat6A Ultra Slim da 1 m Nero, UTP, Rame Puro 34AWG, Cavo di Rete Patch RJ45 Ultra Sottile, Testato Singolarmente. Lunghezza cavo: 1 m, Cavo standard: Cat6a, Schermatura dei cavi: U/UTP (UTP), Connettore 1: RJ-45, Connettore 2: RJ-45, Placcatura contatti: Oro, Velocità di trasferimento dati: 10000 Mbit/s, Colore del prodotto: Nero



Caratteristiche	
Colore del prodotto *	Nero
Lunghezza cavo *	1 m
Cavo standard *	Cat6a
Schermatura dei cavi *	U/UTP (UTP)
Connettore 1 *	RJ-45
Connettore 2 *	RJ-45
Genere del connettore 1 *	Maschio
Genere del connettore 2 *	Maschio
Fattore di forma del connettore 1	Dritto
Fattore di forma del connettore 2	Dritto
Placcatura contatti	Oro
Materiale rivestimento	Elastomero Termoplastico (TPE)
Forma del cavo *	Rotondo
Tipo di conduttore	Intrecciato
Materiale conduttore	Rame
Tecnologia di cablaggio	10GBase-T
Tipo di interfaccia Ethernet	Fast Ethernet, Gigabit Ethernet, 5 Gigabit Ethernet, 2.5 Gigabit Ethernet
Dimensione del cavo AWG	34
Velocità di trasferimento dati	10000 Mbit/s
Frequenza	500 MHz
Connettore antigroviglio per cavo	✔

Caratteristiche	
Plug & Play	✔
Condizioni ambientali	
Intervallo temperatura di funzionamento	-20 - 60 °C
Intervallo di temperatura	-20 - 75 °C
Range di umidità di funzionamento	0 - 90%
Certificati di sicurezza	
Certificati di conformità	RoHS, CE
Dimensioni e peso	
Diametro esterno	2,6 mm
Peso	16 g
Contenuto dell'imballo	
Quantità per pacco	1 pz
Dati su imballaggio	
Larghezza imballo	200 mm
Profondità imballo	140 mm
Altezza imballo	18 mm
Peso dell'imballo	19 g
Dati logistici	
Larghezza scatola principale	460 mm
Lunghezza del cartone principale	300 mm
Altezza scatola principale	200 mm
Quantità per cartone principale	90 pz

065030917704

0065030917704

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 23-SEP-2026. Prints or copies of Information are only valid on the printed Publication date