StarTech.com Cavo USB4 da 3m, Cavo USB-C Certificato USB-IF, 20 Gbps, PD 60W, DP 2.1 4K 120Hz, Cavetto Tipo-C con guaina in TPE, Nero



Marchio : StarTech.com

Codice prodotto: CC3M20GUSB4CX

Nome del prodotto : Cavo USB4 da 3m, Cavo USB-C Certificato USB-IF, 20 Gbps, PD 60W, DP 2.1 4K 120Hz, Cavetto Tipo-C con guaina in TPE, Nero

StarTech Cavo USB4 da 3m, Cavo USB-C Certificato USB-IF, 20 Gbps, PD 60W, DP 2.1 4K 120Hz, Resistente Cavetto Tipo-C con guaina in TPE, Nero
StarTech.com Cavo USB4 da 3m, Cavo USB-C Certificato USB-IF, 20 Gbps, PD 60W, DP 2.1 4K 120Hz, Cavetto Tipo-C con guaina in TPE, Nero. Lunghezza cavo: 3 m. Connettore 1: USB C, Connettore 2: USB C, Versione USB: USB4 Gen 2x2, Massima velocità di trasferimento: 20 Gbit/s, Colore del prodotto: Nero



Caratteristiche	
Versione USB *	USB4 Gen 2x2
Connettore 1 *	USB C
Connettore 2 *	USB C
Genere del connettore 1 *	Maschio
Genere del connettore 2 *	Maschio
Fattore di forma del connettore 1	Dritto
Fattore di forma del connettore 2	Dritto
Dimensione del cavo AWG	28/34
Materiale del rivestimento del cavo	Elastomero Termoplastico (TPE)
Massima velocità di trasferimento	20 Gbit/s
Tipo di cavo	Cavo tondo
Ricarica rapida	✔
Alimentazione USB	✔
Revisione della fornitura di alimentazione USB	3.0
Fornitura di alimentazione USB fino a	60 W
Colore del prodotto *	Nero
Modalità alternativa DisplayPort USB di Tipo C	✔
versione DisplayPort	2.1
Risoluzione massima	3840 x 2160 Pixel

Caratteristiche	
Tempo massimo di refresh	120 Hz
Gestione energetica	
Corrente di ingresso (max)	3 A
Dimensioni e peso	
Lunghezza cavo *	3 m
Diametro del cavo	5,5 mm
Peso	164 g
Dati su imballaggio	
Larghezza imballo	230 mm
Profondità imballo	80 mm
Altezza imballo	30 mm
Peso dell'imballo	191 g
Contenuto dell'imballo	
Quantità per pacco *	1 pz
Condizioni ambientali	
Intervallo temperatura di funzionamento	0 - 60 °C
Intervallo di temperatura	-20 - 60 °C
Certificati di sicurezza	
Certificati di conformità	CE, RoHS
Dati logistici	
Quantità per cartone principale	60 pz
Larghezza scatola principale	500 mm
Lunghezza del cartone principale	340 mm
Altezza scatola principale	320 mm



0065030922685



065030922685

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 23-SEP-2026. Prints or copies of Information are only valid on the printed Publication date